







STC 72+ & IIC 60+

	<p>ACOUSTIC PERFORMANCE</p> <p>74 IIC    73 STC 76 HIIC   25 ΔIIC</p>		<p>MOISTURE PROTECTION</p> <p>MVTR: <b>0.3</b> LBS 1000FT<sup>2</sup> - 24HRS.</p>
	<p>THERMAL PERFORMANCE</p> <p>R Value per inch: <b>4.3</b> FT<sup>2</sup>-F-HR/ BTU</p>		<p>COMPRESSIVE STRENGTH @25%</p> <p><b>≥ 11</b> psi</p>
	<p>FLAMMABILITY</p> <p><b>CLASS A</b></p>		<p>ENVIROMENTAL</p> <p>Mold &amp; Mildew resistant: YES VOCs: Compliant with CA 01350</p>

This data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conversion of measurements in all units, tolerance, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at [www.floormuffler.com](http://www.floormuffler.com) for the most up to date product information, data, and installation instructions.

Let's get social  
f @ v t

floormuffler.com  
1 800 440 6008

